



Your Benefits

- + high safety standards
- + comfortable
- + energy efficient
- + high hose capacities
- + user friendly
- + extremely easy to maintain

FAST. SIMPLE. SAFE.

The BARTH LIFTURMATIC III is distinguished by its excellent performance, safety features, usability and customizable capacity. Due to the touch control unit and safety features. Therefore the LIFTURMATIC III promise a high level of work safety and through the automatic loading and unloading procedures, a very user-friendly procedure. All components are designed to be robust and simple to reduce the cost of daily operation and maintenance.

How does it work?

The LIFTURMATIC III is equipped with an 5,6" Touch Display mounted on the main control unit. Through the digital touch display, the operator will see the capacity before loading or unloading the LIFTURMATIC III. Through the sensors, the system shows the user an alarm, if the operator tries to overload the system. Due to the easy handling of the LIFTURMATIC III, only one operator is needed.

Safety risks are technically impossible.

The LIFTURMATIC III is also equipped with an electronic overload security sensor and a wear resistant electro-mechanical security lock, which is adjusted to the weight of the operator or individual max. weight. Additionally the suspension hook is equipped with an retaining pawl, that doesn't open before the hose is placed in the rail.

Technical Specifications

Product Code	153480 / 153481
Quantity of rails	5 up to 20
System capacity	40 up to 160 hoses with max. 45 / 75 mm (2" / 3") or 12 up to 40 hoses with max. 110 mm (4,5")
Control unit	PLC touch-screen-control, emergency stop switch
Functions	load, unload, rail select, loading status, over-load lock
Lifting speed	max. 20 m / min
Energy	2,9 kW, 230 V

