

<optional company logo>



**Safety Information for  
Lithium Ion Batteries for  
Cordless Power Tools and  
Electric Garden Equipment**



August 2021

**PRELIMINARY REMARKS**

**EC**

These batteries are neither "substances" nor "preparations" according to the REACH Regulation 1907/2006 EC. They have, however, to be regarded as "articles" which are not intended to release substances under normal or reasonably foreseeable conditions of use. Therefore it is not required to provide a Safety Data Sheet according to article 31 of the REACH Regulation (EC) 1907/2006.

**US**

Material Safety Data Sheets (MSDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid or particle;

- (i) which is formed to a specific shape or design during manufacture;
- (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and
- (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard.

**1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY**

**Product Name:**

Lithium-ion Batteries - Rechargeable  
Makita Type : BLXXXX(Y) BLXXXXX(Y) BLXXXX(Y) LXXXX PDCXXXX  
DOLMAR Type : AP-XXX AP-XXXX

**Note:**

XXX : "XXX" represents 3 digit numbers  
XXXX : "XXXX" represents 4 digit numbers  
XXXXX : "XXXXX" represents 5 digit numbers  
(Y) or (YY) : A letter or two letters may be followed after the 4 or 5 digit numbers  
(ex. BL7010, BL1850B, BL1415NA, BL36120A etc.)

Integral Lithium-ion Batteries –Rechargeable  
Makita Cordless Cleaner Type :CLXXXD  
Makita Cordless Screwdriver Type :DFXXXD

**Note:**

XXX : "XXX" represents 3 digit numbers  
(ex. CL105D, DF001D etc.)

**Manufacturer:**

Makita Corporation  
3-11-8, Sumiyoshi-cho, Anjo, Aichi,  
446-8502, Japan  
Phone : +81 (0)566-98-1711  
[www.makita.com](http://www.makita.com)

<optional company logo>



## Safety Information for Lithium Ion Batteries for Cordless Power Tools and Electric Garden Equipment



August 2021

### 2. HAZARDS IDENTIFICATION

Lithium ion batteries have a gas-tight seal and not hazardous when used and handled in accordance with the manufacturer's specifications.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Cathode: Li-, Ni-, Co-, Mn-, Al- containing oxides (active material), polyvinylidene fluoride (binder), carbon (conductive material), additives, aluminium foil

Anode: carbon (active material), silicon monoxide (active material), polyvinylidene fluoride(binder), styrene-butadiene rubber(binder), Carboxymethyl cellulose sodium salt(binder), Organic polymer (binder), additives, copper foil

Electrolyte: organic solvents (non aqueous liquids), lithium salt, additives,

The product does not contain metallic lithium or lithium alloys.

### 4. FIRST AID MEASURES

#### **Skin or eye contact with released substances (electrolyte):**

Rinse eyes thoroughly with water for at least 15 minutes. Seek medical attention.

#### **Chemical Burns:**

Chemical burns require appropriate treatment. Seek medical attention.

#### **Respiratory tract:**

In case of intensive smoke generation or gas release immediately leave the room. In case of large quantities and irritation of the respiratory tract, seek medical attention. Ensure sufficient ventilation.

#### **Swallowing:**

Rinse mouth and vicinity with water. Seek immediate medical attention.

### 5. FIREFIGHTING MEASURES

Fires from lithium batteries can basically be fought with water. There is no need for additional or special extinguishing agents. Surrounding fires can be fought with conventional extinguishing agents. The fire of a battery cannot be considered separately from the surrounding fire.

The cooling effect of water effectively prevents surrounding fire from spreading to batteries which have not yet reached the critical ignition ("thermal runaway") temperature.

Reduce fire load by separating large quantities and moving them away from the area of risk.

During a fire, gases may develop which may cause injuries of the respiratory tract. Take care of sufficient respiratory protection.

### 6. ACCIDENTAL RELEASE MEASURES

When damaged the battery housing may release electrolyte. Seal batteries in an airtight plastic bag, add dry sand, chalk powder (CaCO<sub>3</sub>) or vermiculite. Traces of electrolyte can be absorbed with dry paper towels. Wear protective gloves in order to prevent direct contact with skin. Thoroughly rinse contaminated areas with water.



Use appropriate personal protective equipment (protective gloves, protective clothing, protective mask, respiratory protection).

### 7. HANDLING AND STORAGE

#### **Handling and Occupational Safety**

#### **Handle discharged batteries with care**

Even when discharged, batteries represent a risk as they may deliver a very high short-circuit current. Even if they seem to be discharged lithium ion batteries need to be treated as carefully as if they were not discharged.

<p>&lt;optional company logo&gt;</p> 	<p><b>Safety Information for Lithium Ion Batteries for Cordless Power Tools and Electric Garden Equipment</b></p>	
--	---	---

August 2021

**Avoid impact and physical damage**

Impact and penetration may damage the battery. This may cause leakage, heat generation, smoke, fire, or explosion.

**Keep batteries away from other metal objects**

Paperclips, coins, keys, nails, screws or other metal objects can short the terminals. This may cause burns or fire.

**Under abusive conditions liquid may be released from the battery**

Avoid contact with battery liquids. Rinse with water. Upon contact with eyes, seek also medical assistance. Liquid released from the battery may cause irritation or chemical burns.

**Do not expose a batteries to fire or excessive temperature**

Exposure to fire or temperature above 130 °C may cause fire, explosion and personal injuries. Do not incinerate batteries except for permitted waste incinerators.

**Do not disassemble batteries**

Disassembly or modification of the battery may damage the protection circuit. This may cause heat generation, smoke, fire, or explosion.

**Do not immerse batteries in liquids like water or beverages**

Exposure to liquids may damage the battery. This may cause heat generation, smoke, fire, or explosion.

**Use only chargers recommended by the manufacturer**

Chargers which are not suited for the battery being recharged may be damaged. This may cause fire.

**Use cordless power tools and electric garden equipment only with designated batteries**

Use of cordless power tools and electric garden equipment with other batteries may lead to battery damage. This may cause fire and personal injury.

**Do not use damaged or modified batteries**

Damaged or modified batteries may exhibit unpredictable risks. This may cause fire, explosion and personal injury.

**Do not use defective batteries**

Immediately stop using batteries when abnormalities are noticed, such as smell, heat, discoloration, or deformation. Otherwise the battery may be damaged. This may cause heat generation, smoke, fire, or explosion.

**Storage**

Always carefully observe warning notices on batteries and in instructions for use. Use only recommended battery types.

Lithium batteries preferably are to be stored at ambient temperature and in dry places (max. 50 °C). Large temperature fluctuations are to be avoided. (For example, do not store near heat radiators, do expose to sunlight for sustained periods).

Consult local authorities and insurers when storing large quantities of lithium batteries.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Not applicable. Lithium ion batteries are products, which do not release substances under normal and reasonably foreseeable conditions of use. Therefore there is normally no need for exposure controls and personal protection

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Compact batteries with (plastic) housing, terminals

**10. STABILITY AND REACTIVITY**

When an upper temperature limit of (e.g. 130°C) is exceeded, batteries may rupture or the pressure relief mechanism may be activated.

<optional company logo>



## Safety Information for Lithium Ion Batteries for Cordless Power Tools and Electric Garden Equipment



August 2021

Exceeding a storage temperature of 60 °C may lead to accelerated ageing and premature loss of function.

### 11. TOXICOLOGICAL INFORMATION

Lithium ion batteries are products, which do not release substances under normal and reasonably foreseeable conditions of use. In case of damaged ingredients may be released.

### 12. ECOLOGICAL INFORMATION

Lithium ion batteries do not contain heavy metals (such as lead, cadmium or mercury).

### 13. DISPOSAL CONSIDERATIONS

In the EU, used batteries must not be disposed of with household waste and not be mixed with batteries of other systems in order to prevent risk for man and environment and not to exacerbate recycling.

Used batteries shall be returned (free of charge) to the point of sale or to a collection system (industry, distribution).

According to the EU battery directive, lithium batteries are marked with the symbol indicating 'separate collection' (crossed-out wheeled bin shown below).



To prevent short circuits and associated heating, lithium batteries must not be stored or transported in bulk form and unprotected. Suitable measures against short circuits include:

- Placing the batteries in original packaging or a plastic bag
- Individual protection of battery contacts (e.g. using insulating tape)
- Embedding in dry sand

### 14. TRANSPORT INFORMATION

Commercial transport of lithium ion batteries is subject to dangerous goods regulations. Transport preparations and transport are exclusively to be carried out by appropriately trained personnel and/or the process has to be accompanied by experts with suitable knowledge or qualified companies.

#### Transport regulations:

Lithium batteries are subject to the following dangerous goods regulations and exemptions based on the respective valid revision:

Class 9

UN 3480: LITHIUM ION BATTERIES

UN 3481: LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT,  
(i.e. inserted in battery operated product) or



LITHIUM ION BATTERIES PACKED WITH EQUIPMENT  
(i.e. packed together with battery operated product)

#### ADR, RID

Special provisions: 188, 230, 310, 376, 377, 636

Packing instructions: P903, P908, P909, LP903, LP904

Tunnel category E

<p>&lt;optional company logo&gt;</p> 	<p><b>Safety Information for Lithium Ion Batteries for Cordless Power Tools and Electric Garden Equipment</b></p>	
--	---	---

August 2021

**IMDG Code**

Special provisions: 188, 230, 310, 348, 360, 376, 377

Packing instructions: P903, P908, P909, LP903, LP904

EmS: F-A, S-I

Stowage category A

**ICAO, IATA-DGR**

Special provisions: A88, A99, A154, A164, A181, A182, A183, A185, A201

Packing instructions: 965, 966, 967

**All transport modes**

[Test methods and requirements

In accordance with the dangerous goods regulations for lithium batteries, each new type of cell or battery must have passed all tests listed in the UN Manual of Tests and Criteria, Part III, Section 38.3. This particularly applies also if multiple cells or batteries have been assembled into new batteries (battery packs or battery assemblies). Therefore it should be confirmed here that batteries as distributed by the manufacturer/supplier have passed the respective tests.

These requirements also apply to used batteries. Used batteries that are intact and undamaged can usually be transported under the regulations for unused batteries]

Defective or damaged batteries are subject to more stringent regulations. These regulations may prohibit the transport completely. A general ban applies to air transport (IATA DGR - special provision A154).

For transport of used - but not damaged - batteries please refer to the respective special provisions.

Waste batteries and batteries which are sent for recycling or disposal are prohibited from air transport (IATA Special provision A 183).

Exemptions need to be approved in advance by the competent authority of the country of origin and the respective country of the airline.

**15. REGULATORY INFORMATION**

Regardless of shape, volume, weight and application, batteries, in the EU are subject to the respective national implementation of the European Battery Directive (2006/66/EC). It includes but is not limited to regulations regarding placing on the market, collection, treatment and recycling of batteries.

Transport regulations are according to IATA, ADR, IMDG, RID. Refer to section 14.

**16. OTHER INFORMATION**

This information provides assistance for compliance with legal requirements, but does not replace them. It is based on our present knowledge.

The above information was compiled to the best of our knowledge and belief.

The information does not represent any warranties. Distributors and users of the product have to take their own responsibility to observe applicable laws and regulations.



## LITHIUM BATTERIES TEST SUMMARY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF UN MANUAL OF TESTS AND CRITERIA


1	Product Manufacturer	Makita Corporation 3-11-8, Sumiyoshi-cho, Anjo, Aichi, 446-8502, Japan Phone : +81 (0)566-98-1711 <a href="http://www.makita.com">www.makita.com</a>
2	Model	Detachable Lithium-ion Batteries – Rechargeable Makita Type : BL  Separable Lithium-ion Batteries – Rechargeable Makita Type : PDC  Integral Lithium-ion Batteries – Rechargeable for Makita Cordless Cleaner  Integral Lithium-ion Batteries – Rechargeable for Makita Cordless Screwdriver  For detailed list of models see product test information table
3	Voltage rating	3.6V / 7.2V / 10.8V (12Vmax.) / 14.4V / 18V / 36V (40Vmax.) / 57.6V (64Vmax)
4	Ah rating	1.3Ah / 1.5Ah / 2.0Ah / 2.5Ah / 3.0Ah / 4.0Ah / 5.0Ah / 6.0Ah / 33.5Ah
5	Wh rating	5.4Wh / 10.8Wh / 14.0Wh / 16.2Wh / 17.0Wh / 22.0Wh / 27.0Wh / 28.08Wh / 35.1Wh / 36.0Wh / 44.0Wh / 54.0Wh / 58.0Wh / 72.0Wh / 80.0Wh / 87.0Wh / 90.0Wh / 94.0Wh / 108.0Wh / 144.0Wh / 180.0Wh / 230.2Wh / 288.0Wh / 1206Wh

### List of Tests Conducted and Results

PERFORMED TESTS		RESULTS
38.3.4.1 T1	Altitude Simulation	Passed
38.3.4.2 T2	Thermal Test	Passed
38.3.4.3 T3	Vibration	Passed
38.3.4.4 T4	Shock	Passed
38.3.4.5 T5	External Short Circuit	Passed
38.3.4.7 T7	Overcharge	Passed

(Note that tests T6 and T8 are not applicable to batteries.)



Revision Date: 2021-11-19	Revision Number: 3.0
RESEARCH & DEVELOPMENT PLANNING DEPARTMENT GENERAL MANAGER Yoshihisa Inuzuka	Signature 

The UN 38.3 tests were performed by one of the following test houses and were tested to UN Manual Test and Criteria Revision 3 Amendment 1 or subsequent revisions or amendments.

<p>Tohoku Murata Manufacturing Co., Ltd. 1-1 Shimosugishita, Takakura, Hiwada-machi, Koriyama-shi, Fukushima, 963-0531 Japan Phone: +81-24-955-7770 e-mail: <a href="mailto:tmm-qa-compliance@murata.com">tmm-qa-compliance@murata.com</a> Website: <a href="https://www.murata.com/en-global/group/tohokumurata">https://www.murata.com/en-global/group/tohokumurata</a></p>	<p>Samsung SDI Co., Ltd 467, Beonyeong-ro, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Korea Phone: +82-41-560-3114 e-mail: <a href="mailto:lian55.kim@samsung.com">lian55.kim@samsung.com</a> Website: <a href="http://samsungsdi.co.kr">http://samsungsdi.co.kr</a></p>
<p>CQC Intime Testing Technology Co.,Ltd. East Taihu Technology and Finance City, No.1368 Wuzhong Dadao Rd., Wuzhong Economic Development Zone, Suzhou, Jiangsu. Phone: 0512-66303623 e-mail: <a href="mailto:cqc_jszlb@126.com">cqc_jszlb@126.com</a> Website: <a href="http://www.cqc-it.com">http://www.cqc-it.com</a></p>	<p>Celxpert(Kunshan) Energy Co.Ltd NO.1111,Hanpu Road,Yushan Town,Kunshan City,Jiangsu Province,P.R.China Phone: +86-0512-57775999-8239 e-mail: <a href="mailto:Frank_Gao@cn.celxpert.com">Frank_Gao@cn.celxpert.com</a> Website: <a href="http://www.celxpert.com.tw">http://www.celxpert.com.tw</a></p>
<p>Murata Energy Device Wuxi Co., Ltd. No.27 Changjiang Road, New District,Wuxi,Jiangsu Province, 214028 P.R.C. Phone: +86-510-8523-9120 e-mail: <a href="mailto:mdw-qa-comp@murata.com">mdw-qa-comp@murata.com</a> Website: <a href="https://www.murata.com/en-global/group/tohokumurata">https://www.murata.com/en-global/group/tohokumurata</a></p>	<p>Shanghai Research Institute of Chemical Industry Testing Center No.345 East Yunling Road, Putuo, Shanghai,China Phone: +86-21-3176555 e-mail: <a href="mailto:battery@ghs.cn">battery@ghs.cn</a> Website: <a href="http://www.ghs.cn">http://www.ghs.cn</a></p>
<p>HCT CO.,LTD. 74, Seoicheon-ro 578beon-gil, Majang- myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Phone:031-645-6300 e-mail:<a href="mailto:E_safety@hct.co.kr">E_safety@hct.co.kr</a> Website: <a href="http://www.hct.co.kr/">http://www.hct.co.kr/</a></p>	



## Description of Battery and Test Information

Model numbers	Physical Description	Battery weight (kg)	Wh rating	Test report number	Test report date	Applicable UN Numbers acc. to UN Model Regulations
BL0715 7.2V 1.5 Ah	Detachable cluster lithium-ion accumulator	0.12	10.8	QA-7349	10-Oct-2017	UN3480/ UN3481
BL1013/BL1014 10.8V/12Vmax. 1.3Ah	Detachable cluster lithium-ion accumulator	0.17	14.0	QA-7332 QA-7357	4-Oct-2017 20-Oct-2017	UN3480/ UN3481
BL1013/BL1014 10.8V/12Vmax. 1.3Ah	Detachable slide in lithium-ion accumulator	0.18	14.0	MT0038801	4-Mar-2011	UN3480/ UN3481
BL1015/BL1016 10.8V/12Vmax. 1.5Ah	Detachable slide in lithium-ion accumulator	0.25	17.0	CPK-QA-Lab- UN383PACK1402 CPK-Lab- UN383PACK15060	16-Aug-2014 16-Aug-2015	UN3480/ UN3481
BL1015/BL1016 10.8V/12Vmax. 1.5Ah	Detachable slide in lithium-ion accumulator	0.21	16.2	CPK-Lab- UN383PACK21053-A CPK-Lab- UN383PACK21054-A	05-Aug-2021 07-Aug-2021	UN3480/ UN3481
BL1021B 12Vmax. 2.0Ah	Detachable slide in lithium-ion accumulator	0.24	22.0	CPK-QA-Lab- UN383PACK15063	20-Aug-2015	UN3480/ UN3481
BL1040B/BL1041B 10.8V/12Vmax. 4.0Ah	Detachable slide in lithium-ion accumulator	0.43	44.0	CPK-Lab- UN383PACK14042 CPK-QA-Lab- UN383PACK15062	23-Dec-2014 23-Aug-2015	UN3480/ UN3481
BL1415N 14.4V 1.5Ah	Detachable slide in lithium-ion accumulator	0.32	22.0	SDI-UN-131101-02	17-Dec-2017	UN3480/ UN3481
BL1415NA 14.4V 1.5Ah	Detachable slide in lithium-ion accumulator	0.40	21.6	MT0045738	15-Jul-2011	UN3480/ UN3481
BL1430B 14.4V 3.0Ah	Detachable slide in lithium-ion accumulator	0.50	44.0	SDI-UN-P160118-01	18-Jan-2016	UN3480/ UN348
BL1440 14.4V 4.0Ah	Detachable slide in lithium-ion accumulator	0.53	58.0	QA-7358	20-Oct-2017	UN3480/ UN3481
BL1450 14.4V 5.0Ah	Detachable slide in lithium-ion accumulator	0.51	72.0	SDI-UN-P140807-01	11-Aug-2014	UN3480/ UN348





BL1460A 14.4V 6.0Ah	Detachable slide in lithium-ion accumulator	0.54	87.0	CPK-QA-Lab- UN383PACK15061	12-June-2015	UN3480/ UN3481
BL1460B 14.4V 6.0Ah	Detachable slide in lithium-ion accumulator	0.54	87.0	CPK-QA-Lab- UN383PACK15027	12-June-2015	UN3480/ UN3481
BL1415G 14.4V 1.5Ah	Detachable slide in lithium-ion accumulator	0.33	22.0	CPK-QA-Lab- UN383PACK16008	01-Mar-2016	UN3480/ UN3481
BL1415G 14.4V 1.5Ah	Detachable slide in lithium-ion accumulator	0.32	22.0	CPK-QA-Lab- UN383PACK21006-A	22-Mar-2021	UN3480/ UN3481
BL1420G 14.4V 2.0Ah	Detachable slide in lithium-ion accumulator	0.33	28.08	CPK-Lab- UN383PACK21007- A-1-1	23-Mar-2021	UN3480/ UN3481
BL1815N 18V 1.5Ah	Detachable slide in lithium-ion accumulator	0.36	27.0	MT0059172	15-Feb-2012	UN3480/ UN3481
BL1815N 18V 1.5Ah	Detachable slide in lithium-ion accumulator	0.36	27.0	CPK-QA-Lab- UN383PACK13025	13-Oct-2013	UN3480/ UN3481
BL1820B 18V 2.0Ah	Detachable slide in lithium-ion accumulator	0.38	36.0	QA-7337	5-Oct-2017	UN3480/ UN3481
BL1830B 18V 3.0Ah	Detachable slide in lithium-ion accumulator	0.64	54.0	QA-7344	5-Oct-2017	UN3480/ UN3481
BL1830B 18V 3.0Ah	Detachable slide in lithium-ion accumulator	0.60	54.0	SDI-UN-P160314-01	14-Mar-2016	UN3480/ UN3481
BL1840B 18V 4.0Ah	Detachable slide in lithium-ion accumulator	0.65	72.0	QA-7285	1-Sep-2017	UN3480/ UN3481
BL1840B 18V 4.0Ah	Detachable slide in lithium-ion accumulator	0.60	72.0	SDI-UN-P150209-01	10-Feb-2015	UN3480/ UN3481
BL1850B 18V 5.0Ah	Detachable slide in lithium-ion accumulator	0.64	90.0	QA-7286	1-Sep-2017	UN3480/ UN3481
BL1850B 18V 5.0Ah	Detachable slide in lithium-ion accumulator	0.62	90.0	SDI-UN-P160104-01	4-Jan-2016	UN3480/ UN3481



BL1860B 18V 6.0Ah	Detachable slide in lithium-ion accumulator	0.67	108.0	2017126J17835	7-Dec-2017	UN3480/ UN3481
BL1815G 18V 1.5Ah	Detachable slide in lithium-ion accumulator	0.39	27.0	CPK-QA-Lab- UN383PACK16012	23-Mar-2016	UN3480/ UN3481
BL1815G 18V 1.5Ah	Detachable slide in lithium-ion accumulator	0.38	27.0	CPK-Lab- UN383PACK21003-A	03-Mar-2021	UN3480/ UN3481
BL1820G 18V 2.0Ah	Detachable slide in lithium-ion accumulator	0.39	35.1	CPK-Lab- UN383PACK21004- A-1-1-1-1-1	09-Mar-2021	UN3480/ UN3481
BL3626 36V 2.6Ah	Detachable slide in lithium-ion accumulator	1.34	94.0	QA-7346	6-Oct-2017	UN3480/ UN3481
BL3622A 36V 2.2Ah	Detachable slide in lithium-ion accumulator	1.33	80.0	QA-7348	6-Oct-2017	UN3480/ UN3481
Integral Batteries for DF001D	Integral lithium- ion accumulator	0.13	5.4	CPK-QA-Lab- UN383PACK16026	26-Dec-2016	UN3480/ UN3481
Integral Batteries for CL105D / CL110D	Integral lithium- ion accumulator	0.18	14.0	CPK-QA-Lab- UN383PACK13028- K092-1-1	18-May-2014	UN3480/ UN3481
Integral Batteries for CL104D / CL111D	Integral lithium- ion accumulator	0.18	17.0	CPK-QA-Lab- UN383PACK16022-1- 1-1-1	27-Feb-2018	UN3480/ UN3481
BL1020V 10.8V/12Vmax. 2.0Ah	Integral lithium- ion accumulator	0.185	22.0	CPK-Lab- UN383PACK20004-A	21-Feb-2020	UN3480/ UN3481
BL4025 40Vmax. 2.5Ah	Detachable slide in lithium-ion accumulator	0.70	90.0	MDW-B19090	12-Sep-2019	UN3480/ UN3481
BL4040 40Vmax. 4.0Ah	Detachable slide in lithium-ion accumulator	1.04	144.0	1119040200	20-May-2019	UN3480/ UN3481
BL4020 40Vmax. 2.0Ah	Detachable slide in lithium-ion accumulator	0.68	72.0	1120010340	27-Feb-2020	UN3480/ UN3481
BL4050F 40Vmax. 5.0Ah	Detachable slide in lithium-ion accumulator	1.31	180.0	1120050246	28-Jun-2020	UN3480/ UN3481



BL4080F 40Vmax. 8.0Ah	Detachable slide in lithium-ion accumulator	1.90	288.0	1121030246	16-Apr-2021	UN3480/ UN3481
PDC1200 36V 33.5Ah	Separable lithium-ion accumulator	8.80	1206	HCT-BA-2002-RE016	13-Feb-2020	UN3480/ UN3481
BL6440 57.6V 4.0Ah	Separable lithium-ion accumulator	2.20	230.2	1120090534	28-Sep-2020	UN3480/ UN3481