Panasonic Batteries

Panasonic Industrial Company A Division of Panasonic Corporation of North America 5201 Tollview Drive, 1F-3 Rolling Meadows, IL 60008 Toll Free: 877-726-2228 Fax: 847-468-5750 Internet: www.panasonic.com/industrial/batteries-oem e-mail: <u>oembatteries@us.panasonic.com</u> Product: Lithium-ion Batteries (Li-ion) Applicable models/sizes: All Cylindrical and Prismatic Lithium-ion batteries

Revision: - January 1, 2020

The batteries referenced herein are exempt articles and are <u>not</u> subject to the OSHA Hazard Communication Standard requirement. This sheet is provided as a service to our customers.

<u>SDS</u>

Safety Data Sheets (SDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid or particle; (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempt from the requirements of the Hazard Communication Standard, hence a SDS is not required.

The following components are found in a Panasonic Lithium Ion battery:

Lithium Cobalt Oxide Type - LCO

Component	Material	Fo	rmula / CAS
Positive Electrode	Lithium Cobalt Oxide - LCO	LiCoO ₂	12190-79-3
Negative Electrode	Graphite	С	7440-44-0
Electrolyte	Ethylene Carbonate – Solvent	C ₃ H ₄ O ₃	96-49-1
	Diethyl Carbonate – Solvent	$C_5H_{10}O_3$	105-58-8
	Lithium Hexaflurophosphate – Salt	LiPF ₆	21324-40-3



DISPOSAL

All Panasonic Lithium ion batteries are classified by the federal government as non-hazardous waste and are safe for disposal in the normal municipal waste stream. These batteries, however, do contain recyclable materials. Panasonic is a Licensee of the Call2Recycle Battery Recycling Program. If you build our cells into a battery pack, please call 1-800-8-BATTERY or go to the Call2Recycle website at <u>www.call2recycle.org</u> for additional information on how your branded product can also participate in the program.

TRANSPORTATION

All Panasonic lithium ion batteries are not subject to the other requirements of the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.

Effective January 1, 2020 all Panasonic lithium ion batteries can be shipped by air in accordance with International Civil Aviation Organization (ICAO) 2019-2020 edition, Section II or Section 1B or International Air Transport Association (IATA), 61th edition, Section II or 1B, Packing Instructions (PI) 965 (Batteries), PI 966 (Batteries, packed with equipment) and PI 967 (Batteries, contained in equipment) as appropriate.

<u>Notice</u>: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Industrial Company makes no warranty expressed or implied. All Panasonic lithium ion batteries are regulated by the International Maritime Organization (IMO), 2018 edition, 39th amendment, under Special Provisions 188 and 230.

All Panasonic lithium batteries are regulated by the ADR, 2019-2020 Edition under SP 188 and the TDG by SP34.

All Panasonic lithium ion cells are tested and comply with the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3.

If you build any of our lithium ion cells into a battery pack, you must also assure that they are tested in accordance with the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3, 6th Revised Edition, Amendment 1..

If you plan on transporting any untested prototype battery packs contact your Panasonic Sales Representative for regulatory information. Check with your air carrier before shipping. Many air carriers have additional requirements.

FIRST AID

If you get electrolyte in your eyes, flush with water for 15 minutes without rubbing and immediately contact a physician. If you get electrolyte on your skin wash the area immediately with soap and water. If irritation continues, contact a physician. If the battery is ingested, call the Rocky Mountain Poison and Drug Center at 800-498-8666 for the US and Canada or 303-389-1300 internationally or your local poison center immediately.

GENERAL RECOMMENDATIONS

CAUTION: Risk of fire, explosion and burns. Do not short-circuit, crush, incinerate or disassemble battery.

FIRE SAFETY

In case of fire, you can use dry chemical, alcohol resistant foam (ARAFFF type) or carbon dioxide fire extinguishers. Cooling the exterior of the batteries with copious amounts of water will help prevent propagation and rupturing. Fire fighters should use self-contained breathing apparatus. Detailed information on lithium ion battery fires can be found in Guide 147 (Lithium Ion Batteries) of the US DOT Emergency Response Guide.

<u>Notice</u>: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Industrial Company makes no warranty expressed or implied.

	t Summary Report lel Regulations and sub-section 38.3 of Manual of Tests and Criteria, Part III, subsection 38.3.5 [d] Unique report ID: UN.PB.PA-L2125.D, UN38.3, Rev.6
PA-L2125.D Same Type Part #: as listed below	[e] Date of test report: 2017-05-22
[b] Manufacturer Fey Elektronik GmbH Storchenweg 3 21217 Seevetal Germany info@feyelektronik.de T. +49 40 703 8888-0 www.feyelektronik.de	[c] Test Laboratory Fey Elektronik GmbH Storchenweg 3 21217 Seevetal Germany info@feyelektronik.de T. +49 40 703 8888-0 www.feyelektronik.de
✓ Same Type Part Numbers # (all): PA-L2125.R007	
	Cell 🖸 Battery
 [f] (iii) ☑ Watt-hour rating: 24 Wh or □ Note: The watt-hours of the same part numbers may v. [f] (v) Model number(s): PA-L2125.D [f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured accordit 	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF
 [f] (iii)	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 vo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System.
iii) Watt-hour rating: 24 <	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. : (Pass / Fail / N.A.) Remark
f] (iii) Watt-hour rating: 24 Wh or Note: The watt-hours of the same part numbers may watter. f] (v) Model number(s): PA-L2125.D f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-tests Our batteries/products are manufactured according For further information visit our website. g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. : (Pass / Fail / N.A.) Remark Pass
f] (iii) ☑ Watt-hour rating: 24 Wh or □ Note: The watt-hours of the same part numbers may weight f] (v) Model number(s): PA-L2125.D f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured according For further information visit our website. g] List of Tests Conducted Result	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 vo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. (Pass / Fail / N.A.) Remark Pass Pass
f] (iii) ☑ Watt-hour rating: 24 Wh or □ Note: The watt-hours of the same part numbers may weet f] (v) Model number(s): PA-L2125.D f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured according For further information visit our website. g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation 38.3.4.2 Test T.2: Thermal test 38.3.4.3 Test T.3: Vibration	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. (Pass / Fail / N.A.) Remark Pass Pass Pass Pass
f] (iii) I Watt-hour rating: 24 Wh or I Note: The watt-hours of the same part numbers may with the same part numbers and with the same part numbers and with the same part numbers may with the same part numers may with the same part numbers may withe	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 vo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. (Pass / Fail / N.A.) Remark Pass Pass
f] (iii) ☑ Watt-hour rating: 24 Wh or □ Note: The watt-hours of the same part numbers may weet f] (v) Model number(s): PA-L2125.D f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured according For further information visit our website. g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation 38.3.4.2 Test T.2: Thermal test 38.3.4.3 Test T.3: Vibration 38.3.4.4 Test T.4: Shock 38.3.4.5 Test T.5: External short circuit 38.3.4.6 Test T.6: Impact/Crush	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. Clease / Fail / N.A.) Remark Pass
f] (iii) [] Watt-hour rating: 24 Wh or [] Note: The watt-hours of the same part numbers may watter. f] (v) Model number(s): PA-L2125.D f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured according For further information visit our website. g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation 38.3.4.2 Test T.2: Thermal test 38.3.4.3 Test T.3: Vibration 38.3.4.4 Test T.4: Shock 38.3.4.5 Test T.5: External short circuit 38.3.4.6 Test T.6: Impact/Crush 38.3.4.7 Test T.7: Overcharge	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 vo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. (Pass / Fail / N.A.) Remark Pass N.A. for cell testing only Pass n.a. for primary cells or batteries
[f] (iii) [] Watt-hour rating: 24 Wh or [] Note: The watt-hours of the same part numbers may with the watt-hours of the same part numbers may with the work of the same part numbers may with the same part numbers are manufactured according to the same part numbers are manufactured according for further information visit our website. g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation 38.3.4.2 Test T.2: Thermal test 38.3.4.3 Test T.3: Vibration 38.3.4.4 Test T.4: Shock 38.3.4.4 Test T.4: Shock 38.3.4.5 Test T.5: External short circuit 38.3.4.7 Test T.7: Overcharge 38.3.4.8 Test T.8: Forced discharge	Lithium content: g vary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 vo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. (Pass / Fail / N.A.) Remark Pass N.A. for cell testing only Pass N.A. for cell testing only Pass n.a. for primary cells or batteries N.A. for cell testing only
 [f] (iii) ☑ Watt-hour rating: 24 Wh or □ Note: The watt-hours of the same part numbers may we [f] (v) Model number(s): PA-L2125.D [f] (iv) Physical description: Hardcase-Pack with two Nominal Voltage: 3,6V Used and UN38.3-test Our batteries/products are manufactured according For further information visit our website. [g] List of Tests Conducted Result 38.3.4.1 Test T.1: Altitude simulation 38.3.4.2 Test T.2: Thermal test 38.3.4.4 Test T.4: Shock 38.3.4.5 Test T.5: External short circuit 38.3.4.7 Test T.7: Overcharge 38.3.4.8 Test T.8: Forced discharge 	Lithium content: g yary by +/- 20 percent from the above value according to UN38.3.2.2 (b). Customer Part No.: 8325810 wo cells in a parallel configuration and protective device. /, Nominal Capacity: 6,5Ah typical ted cell type: Panasonic, NCR-18650BF ling to a Quality-Management-System. Clease / Fail / N.A.) Remark Pass Pass Pass Pass Pass Pass Pass Pass Pass N.A. for cell testing only Pass n.a. for primary cells or batteries N.A. for cell testing only Pass. 0.1 UN38.3.3 (g)

Fey Elektronik GmbH, Storchenweg 3, 21217 Seevetal, Germany Tel.: +49 40 703 8888-0 www.feyelektronik.de

Fey Elektronik consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement,



Signature: