

SAFEX® -NEBELGERÄT

Fog Generator

SNG'16 FW

Technische Daten - *Technical data*
(Stand 03.04)

The first theatre fog machine, based on the nowadays standard water based theatrical fog invented by SAFEX was the SAFEX SNG. Since 1973 this machine is the longest approved theatre fog machine world wide.

It is one of the most powerful, rigid and safe fog generating equipment available. SAFEX keeps spare parts in there shelves for minimum 10 years, but we help customers out with it much longer.



The 3250 watts heat exchanger produces a tremendous output of clean and safe fog, a nozzle protection, remote control plug and the output regulator are standards. The machine can be on duty 24 hours a day without any risk.

Elektrische Kenndaten: <i>Electrical data:</i>	230 Volt AC / 50 Hz – 3250 W – Sicherung: 16 Amp. -mittelträge <i>230 Volt AC / 50 Hz – 3250 W – Fuse: 16 Amp. -semi time-lag</i>
Länge: <i>Length:</i>	450 mm (Düse/FS-Anschluß + 115 mm) <i>(Nozzle/Remote control socket + 115 mm)</i>
Breite: <i>Width:</i>	216 mm
Höhe: <i>Height:</i>	225 mm (mit Griff 262 mm - <i>with handle 262 mm</i>)
Gewicht: <i>Weight:</i>	12,5 kg
Tank: <i>Tank:</i>	1,7 Liter , extern beliebig – <i>1,7 litres, external unrestricted</i>
Aufheizzeit: <i>Heating up time:</i>	ca. 6,5 Minuten - <i>approx. 6,5 minutes</i>
Nebelfluidverbrauch: <i>Fog fluid consumption:</i>	max. 145 ml/min.
Nebelerzeugung: <i>Fogging power</i>	ca. 1000 cbm (Sichtweite von 0,5 mtr. in einem Raum von 5 x 8 x 2,5 mtr.) bzw. ca. 4500 cbm innerhalb von 3 min. (Sichtweite von 3 m) <i>approx. 1000 m³ (visibility of 0,5 m in a room of 5 x 8 x 2,5 m) resp. approx. 4500 m³ within 3 min. (visibility of 3 m)</i>
Fernsteueranschluß: <i>Remote control:</i>	230 Volt –5-polige Fernsteuer-Dose aus GFK - Niedervolt möglich! <i>5-pole remote control socket - low voltage possible!</i>
Zubehör: <i>Accessories:</i>	3 m. Gummi-Netzkabel , Ansaugschlauch und Filter, Gebrauchsanweisung , Tankdeckel (Kanister) mit Ansaugschlauch <i>3 m flexible power cord, tank holder, suction hose and filter, instruction manual, external tank lid (canister) with suction hose</i>
Sonderzubehör: <i>Optional accessories:</i>	verschiedene Fernsteuergeräte, Nebelkühler, Schlauchadapter, Spezialschlauch, FOG & GO Adapter usw. <i>several remote controls, fog cooler, hose adaptor, ducting hose, FOG & GO adapter etc.</i>
Nebelflüssigkeit: <i>Fog fluid:</i>	Alle SAFEX®-INSIDE-NEBEL- und FOG & GO-Fluide (Nach DIN/VDE 0700 Teil 245 # 32.1) <i>All SAFEX®-INSIDE-FOG- and FOG & GO fluids</i> (According to DIN/VDE 0700 part 245 # 32.1)